

I. PRODUCT AND MANUFACTURER IDENTIFICATION

Product Name	<i>Xylene</i>	
Manufacturer	Concrete Floor Supply.	
Address	13024 2 nd Street Suite A Grandview, MO 64030 U.S.A.	
Emergency Phone	816-533-4837	
Information Phone	816-533-4837	
Email	marketing@concretefloorsupply.com	
Website	www.concretefloorsupply.com	Date Revised December 9, 2016

II. HAZARDOUS IDENTIFICATION

Signal Word: DANGER

Hazard Classification:

Flammable liquids, Category 3

Acute toxicity, Category 5, Oral

Acute toxicity, Category 4, Dermal

Acute toxicity, Category 4, Inhalation

Skin corrosion/irritation, Category 2

Serious eye damage/eye irritation, Category 2A

Aspiration hazard, Category 1

Specific target organ toxicity - single exposure, Category 3, Respiratory tract irritation
Acute hazards to the aquatic environment, Category 2

Hazard Statements:

Hazard Pictograms:



H225 - Highly flammable liquid and vapor.

H332 - Harmful if inhaled.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H303 - May be harmful if swallowed.

H304 - May be fatal if swallowed and enters airways.

H335 - May cause respiratory irritation.

H401 - Toxic to aquatic life.

Precautionary Statements:

P210 – Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P223 – Keep away from any possible contact with water, because of violent reaction and possible flash fire. P241 – Use explosion-proof electrical/ventilating/lighting/equipment.

P242 – Use only non-sparking tools.

P261 – Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 – Wash hands thoroughly after handling.

P270 – Do not eat, drink or smoke when using this product.

P271 – Use only outdoors or in a well-ventilated area.

P280 – Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements Continued:

P301 + P312 – IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P302 + P352 – IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 + P353 – IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 – IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P330 – Rinse mouth.

P362 – Take off contaminated clothing and wash before reuse.

P370 + P378 – In case of fire: Use for extinction.

P403 + P233 – Store in a well-ventilated place. Keep container tightly closed.

P405 – Store locked up.

P501 - Dispose of contents/container to an approved waste disposal plant.

III. HAZARDOUS INGREDIENTS/IDENTIFICATION INFORMATION

Hazardous Components:	CAS NUMBER	Percentage %
Ortho-Xylene	95-47-6	100%

IV. FIRST AID MEASURES

General Information: Keep victim calm. Obtain medical treatment immediately.

After inhalation: DO NOT DELAY. Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.

After skin contact: Remove contaminated clothing. Immediately flush skin with large amounts of water and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

After eye contact: Immediately flush eyes with large amounts of water for at least 15 minutes while holding eyelids open. Transport to the nearest medical facility for additional treatment. After ingestion: If swallowed, do not induce vomiting; transport to nearest medical facility for

additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3° C), shortness of breath, chest congestion or continued coughing or wheezing. Give nothing by mouth.

Most Important Symptoms and Effects:

Acute: As above.

Delayed: Skin contact.

V. FIRE AND EXPLOSION HAZARD DATA

Suitable Extinguishing Media: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable Extinguishing Media: Do not use water in a jet.

Fire Hazard: DIRECT FIRE HAZARD. Highly flammable. Gas/vapor flammable with air within explosion limits. INDIRECT FIRE HAZARD. May be ignited by sparks. Gas/vapor spreads at floor level: ignition hazard.

Explosion Hazard: DIRECT EXPLOSION HAZARD. Gas/vapor explosive with air within explosion limits. INDIRECT EXPLOSION HAZARD. Heat may cause pressure rise in tanks/drums: explosion risk. may be ignited by sparks.

Reactivity: Not reactive

Products of Combustion: CO, Organic vapors.

Special Hazards Arising from the Substance or Mixture: Over heated or burning product will boil off flammable fumes and heavy smoke.

Special Remarks and Advice for Firefighters: Cool containers with water spray. Wear self-contained breathing apparatus and firefighter's protective clothing.

VI. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Isolate hazard area and deny entry to unnecessary or unprotected personnel. Stay upwind and keep out of low areas.

Methods and material for containment and cleaning up:

Spill Response: For small liquid spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely.

Remove contaminated soil and dispose of safely.

Waste Disposal: See Above.

Environmental precautions: Remove all possible sources of ignition in the surrounding area. Attempt to disperse the vapor or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ventilate contaminated area thoroughly.

VII. PRECAUTIONS FOR SAFE HANDLING AND USE

Handling

Precautions for safe handling: Avoid inhaling vapor and/or mists. Avoid contact with skin, eyes and clothing. Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. The vapor is heavier than air. Beware of accumulation in pits and confined spaces. Use local exhaust ventilation if there is risk of inhalation of vapors, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials to prevent fires. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge can accumulate, electrostatic discharge and ignition of flammable air-vapor mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to mixing, filtering, and splash filling.

Section VII Continued:

Additional Hazards: Product is HIGHLY FLAMMABLE. Beware of accumulation in pits and confined spaces. Electrostatic discharge may cause fire. The vapors in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Hygiene Measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.

Storage

Storage Conditions: Store in the original container, tightly sealed.

Storage Area: Store at room temperature.

Incompatible Products and Materials: Strong oxidizers.

VIII. EXPOSURE CONTROL MEASURES

Exposure Limits: PEL - 100ppm

Appropriate Engineering Controls: Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits. Eye washes and showers for emergency use.

Personal Protective Equipment:



Hand: Protective Gloves. Wear gloves of adequate length to offer appropriate skin protection from splashes. Longer term protection: Viton. Incidental contact/Splash protection: Nitrile rubber. Eye: Safety Glasses/Goggles Skin and Body: None required.

Respiratory: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation

Additional Information: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances

IX. PHYSICAL AND CONTROL CHARACTERISTICS

Appearance	Form: Liquid Color: Colorless Odor: Solvent
pH-value	NA
Boiling Point	$\geq 145^{\circ}\text{C}$
Auto Igniting	Product is not self-igniting
Vapor Pressure	882 Pa at 25°C
Vapor Density	883-885 kg/m
Viscosity	NE
Solubility	Ca. 0.2 kg/m
Evaporation Rate	NE
Flammability	Flammable
Decomposition Temperature	NE

X. REACTIVITY DATA

Conditions to be avoided: Stable under normal conditions of use. Avoid heat, sparks, open flames and other ignition sources. Prevent vapor accumulation.

Incompatible materials: Strong oxidizing agents.

Hazardous Decomposition Products: CO, Organic vapors.

Reactivity: Not reactive.

Chemical Stability: Stable.

Possibility of Hazardous Reactions: None known.

XI. TOXICOLOGICAL INFORMATION

Acute toxicity: May be harmful if swallowed. Harmful in contact with skin. Harmful if inhaled. Likely Route of Exposure:

Exposure Symptoms:

- Eyes: Serious eye irritation.
 - Skin: Irritation, drying.
 - Inhalation: Inhalation of vapors or mists may cause irritation to the respiratory system.
- Ingestion: May be fatal if swallowed and enters airways.

Effects (Short-term, Long-term):

- Immediate: Inhalation.
- Delayed: Skin and eye.
- Chronic: None known.

Carcinogenicity: No

XIII. DISPOSAL CONSIDERATION

Recommendation: Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses. Waste product should not be allowed to contaminate soil or water. Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

XIV. TRANSPORTATION INFORMATION


UN-Number: 1307
UN Proper Shipping Name: Xylenes
Transport Hazard Class: Flammable - 3
Packing Group: III
Environmental Hazards: Marine pollutant.
Additional Information: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with about transport.



Special Precautions for User:

XV. OTHER REGULATORY INFORMATION

NFPA Ratings (Scale 0-4)



Health: 2

Fire: 4

Reactivity: 0

XVI. OTHER INFORMATION

NOTE: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.
End of SDS.