

# ENVIRO WB SEALER

## WATER BASED SEALER FOR ENVIRO STAINS

Enviro WB sealer is a tough non-yellowing acrylic sealer for use to protect surfaces decorated with Enviro WB stains. Can be used both indoors and outdoors.

<b>Type:</b>	Water dispersed acrylic polymer coating
<b>Toxicity:</b>	Non-Toxic
<b>VOCs:</b>	Less than 100gm per L
<b>Flammability:</b>	Non- Flammable
<b>Composition:</b>	Acrylic copolymer emulsion
<b>Color:</b>	Colorless
<b>Odor:</b>	Slight
<b>Coverage:</b>	250-300 square feet per gallon



NOTE: COVERAGE RATES MAY VARY DEPENDING ON POROSITY, TEXTURE, APPLICATION METHOD AND PRIOR SEALER APPLICATION. EXCESS BUILDUP SHOULD BE AVOIDED.

## PRODUCT HIGHLIGHTS

- **Non-Flammable:** Enviro WB Sealer has no flammable hazard when used indoors or out.
- **No hazardous fumes or odors:** It is not necessary to wear a protective breathing apparatus and normal ventilation is adequate.
- **Fast Drying:** Enviro WB sealer dries to the touch in 30-45 minutes, and it can be recoated in one hour. Two coats are recommended, but the floor can be walked on the same day, usually after 12 hours.
- **Non-Slip and Water Resistant:** The coating is not glossy, and does not present a hazardous walking surface wet or dry.
- **For indoor use,** we recommend the product Ez Glo Polish 48 hours after Enviro WB Sealer has dried. Ez-Glo Polish produces another layer of protection which is a renewable wear surface. Therefore, with normal, easy maintenance Enviro WB Sealer will never wear out or need replacing

## PRODUCT USES

Enviro WB sealer is used as a final protective coating over Water based stained concrete floors, countertops, etc. for use indoors and out with low odor and no flammable hazard.