

CRETE SEAL PLUS EXT

SILOXANE MODIFIED METHYL METHACRYLATE SEALER – HIGH GLOSS

Crete Seal Plus EXT is a non-yellowing, high gloss Siloxane Modified Methyl Methacrylate with excellent adhesion to unsealed or untreated. Formulated to provide superior water and salt resistance compared to standard sealers used to protect exterior concrete. .

Type:	Non-Yellowing, High Gloss MMA Sealer
Toxicity:	Harmful if swallowed
VOC's	<350 g/l
Color:	Clear
Odor:	Slight
Composition:	Siloxane Modified Methyl Methacrylate
Coverage:	Approximately 150-00 square feet per gallon.



NOTE: COVERAGE RATES MAY VARY DEPENDING ON POROSITY, TEXTURE, APPLICATION METHOD AND PRIOR SEALER APPLICATION. EXCESS BUILDUP SHOULD BE AVOIDED.

PRODUCT HIGHLIGHTS

- Minimizes damage due to water and salt water from de-icing road salts and salt water pools.
- Excellent adhesion to clean, unsealed new or old concrete.
- Non-Yellowing though Siloxane Methyl Methacrylate.
- Can be applied as a reseat on certain CFS brand solvent based acrylic sealers or equivalent.
- VOC Compliant formula to meet EPA aim regulations within the US and Canada for concrete cure and seals.

PRODUCT USES

It is recommended to use Crete Seal Plus EXT. for use on new or existing pool decks, stamped concrete, stenciled concrete, acid stained concrete, overlaid concrete, exposed aggregate concrete, broom and trowel finished concrete.

DRY TIMES

Dry Time: 30 mins to 1 hour

Recoat Time: 4-24 Hours

Foot Traffic: 4-6 Hours