



Cherry Glo Matte is a cherry scented water based acrylic floor wax. It is perfect for small areas as well as large commercial areas as it can be applied by dust mop or high speed burnishing. Cherry Wax Matte Finish yields superior long term wear characteristics. Its superior resistance to wet and dry traffic wear can yield a smooth low gloss, matte finish look for months without maintenance.



PRODUCT HIGHLIGHTS

- Pleasant Cherry Scent
- Provides superior protection and resistance to abrasion and scuffing.

Typical Properties & Technical Information

PROPERTY	VALUE
Solids/Active Content, Percentage by weight	21% +/- 1%
Dry Time - Tack Free	1 - 2 Hours
Dry Time - Foot Traffic	12 - 24 Hours
Dry Time - Heavy Traffic	24 - 48 Hours
Re-Coat Time Window	1 - 3 Hours
Application Temperature	50°F - 80°F
VOC (Volatile Organic Compound) Content	0 grams/Liter
Appearance - Wet	Milky White
Appearance - Dry	Clear and Matte



WATER BASED



LOW VOC



LOW ODOR



EASY APPLICATION



INTERIOR



QUICK RETURN
TO SERVICE



MATTE

APPROXIMATE COVERAGE RATES

First Coat: 1000 ft² per gallon

Additional Coats: 1000 ft² per gallon

*Coverage rates may vary depending upon surface porosity, texture, application method and prior sealer application. Excessive build up should be avoided.

Shelf Life

Cherry Glo Matte has a shelf life of up to 1 year in an unopened container.

Packaging

Cherry Glo Matte is available in 1 gallon, 5 gallon and 55 gallon containers

Instructions For Use

Application

1. Do not apply by pouring directly onto surface. Use a plastic roller pan. Apply by microfiber dust mop, synthetic fiber wax applicator, or lambs wool applicator.
2. Apply at a rate of 1,000 square feet per gallon in very thin coats only. Apply in one direction to a consistent, even, and uniform finish. If puddling or pinholes appear, work them out into a thin coat.
3. Allow to dry 1-3 hours. Repeat process as many times as necessary to achieve required finish.

**Spray buffing and/or burnishing is not recommended for matte finish wax as it may result in inconsistent sheen. Maintenance coats may be necessary every once in a while as traffic will eventually wear the surface. Simply mop the area clean using a light, pH neutral detergent solution (See Concrete Cleaner by Surfcoat). Allow to dry and then apply a coat of wax to rejuvenate the smooth finish.

Warning: When applying wax over a newly sealed surface, allow 3-5 days with proper ventilation prior to wax application. Failure to allow this window could result in blushing of the wax.

PLEASE NOTE: It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application. Coverage rates may vary for all coatings and substrates depending on porosity, density, texture etc. **DO NOT USE ON BRICK.**

Clean Up

Use soap and water. Dispose of containers in accordance with local, state and federal regulations.

Product Removal

Product may be re-coated up to 100 times. When product removal is necessary, use a light ammonia and water solution or commercial wax stripper to strip the waxed area back to the sealed surface.

Precautions and Limitations

- This product will freeze during storage. Store at temperatures above 40°F.
- All HVAC ventilation ducts should be somehow blocked prior to application so solvent fumes are not distributed.
- Do not allow this product to be subjected to any form of moisture for 18-24 hours after application.
- It is not recommended to apply product over carpet, tile, or other types of floor adhesives.
- This product performs best when applied in very light coats. Do not puddle or apply in thick coats.
- Please be aware that this product when cured may be slippery when wet.
- This product is not resistant to brake fluid, gasoline, and many similar products.
- This product is not resistant to hot tire pick up.
- This product may darken the surface of many new and existing concrete slabs. Test prior to use.
- This product is harmful if swallowed. Abide by recommended safety guidelines.
- This product was designed for interior, foot traffic use only. It is not recommended for exterior use.
- This product should only be diluted for spray buffing only. Do not dilute for normal use.
- This product should only be used as a sacrificial coating and not used as a sealing compound.

Special Notes

Please consult Safety Data Sheets (SDS) and read warranty information prior to use. This information can be requested by contacting customer service at 844-599-2319.