



Cherry Glo Gloss is a cherry scented, water based interior acrylic floor wax. It is perfect for small areas as well as large commercial areas as it can be applied by dust mop or high speed burnishing. Cherry Wax yields rapid gloss build along with superior long term wear characteristics. Its superior resistance to wet and dry traffic wear can yield a smooth polished look for months without maintenance.



## PRODUCT HIGHLIGHTS

- Pleasant Cherry Scent
- Provides superior protection and resistance to abrasion and scuffing.

## Typical Properties & Technical Information

PROPERTY	VALUE
Solids/Active Content, Percentage by weight	21% +/- 1%
Dry Time - Tack Free	1 - 2 Hours
Dry Time - Foot Traffic	12 - 24 Hours
Dry Time - Heavy Traffic	24 - 48 Hours
Re-Coat Time Window	1 - 3 Hours
Application Temperature	50°F - 80°F
VOC (Volatile Organic Compound) Content	0 grams/Liter
Appearance - Wet	Milky White
Appearance - Dry	Clear and High Gloss



WATER BASED



LOW VOC



LOW ODOR



EASY APPLICATION



INTERIOR



QUICK RETURN  
TO SERVICE



GLOSS

## APPROXIMATE COVERAGE RATES

First Coat: 1000 ft<sup>2</sup> per gallon

Additional Coats: 1000 ft<sup>2</sup> per gallon

\*Coverage rates may vary depending upon surface porosity, texture, application method and prior sealer application. Excessive build up should be avoided.

## Shelf Life

Cherry Glo Gloss has a shelf life of up to 1 year in an unopened container.

## Packaging

Cherry Glo Gloss is available in 1 gallon, 5 gallon and 55 gallon containers

## Instructions For Use

**Surface Prep:** Allow any coatings to fully cure for at least 3-5 days prior to applying wax. Be sure the area of the concrete to be removed is free of trash and debris. Protect all other areas. Mask off all adjacent surfaces with painter's tape or plastic duct tape. If spray buffing, use a plastic or coated cardboard as a spray shield.

**Mixing:** Stir well before using. Material may separate during long term storage. Do Not Thin!

### Application:

1. Do not apply by pouring directly onto surface. Use a plastic roller pan. Apply by microfiber dust mop, synthetic fiber wax applicator, or lambs wool applicator.
2. Apply at a rate of 1,000 square feet per gallon in very thin coats only. Apply in one direction to a consistent, even, and uniform finish. If puddling or pinholes appear, work them out into a thin coat.
3. Allow to dry 1-3 hours. Repeat process as many times as necessary to achieve required finish.

If spray buffing, dilute wax 1:2 with water. Apply using a trig mist sprayer over a small area at a time. Buff that area with a 300 - 500 RPM buffer in a side to side motion until the liquid has disappeared and a superior shine is left. Continue this same process throughout the whole floor.

If burnishing, allow wax to dry thoroughly. Using a 1000 - 3000 RPM burnishing machine, work in a front to back line with a natural hair or synthetic material burnishing pad.

Maintenance coats may be necessary every once in a while as traffic will eventually dull the surface. Simply mop the area clean using a light, pH neutral detergent solution. Allow to dry and then apply a coat of wax to rejuvenate the smooth finish.

Warning: When applying wax over a newly sealed surface, allow 3-5 days with proper ventilation prior to wax application. Failure to allow this window could result in blushing of the wax.

**PLEASE NOTE:** It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application. Coverage rates may vary for all coatings and substrates depending on porosity, density, texture etc. DO NOT USE ON BRICK.

## Clean Up

Use soap and water. Dispose of containers in accordance with local, state and federal regulations.

## Product Removal

Product may be re-coated up to 100 times. When product removal is necessary, use a light ammonia and water solution or commercial wax stripper to strip the waxed area back to the sealed surface.

## Precautions and Limitations

- This product will freeze during storage. Store at temperatures above 40°F.
- All HVAC ventilation ducts should be somehow blocked prior to application so solvent fumes are not distributed.
- Do not allow this product to be subjected to any form of moisture for 18-24 hours after application.
- It is not recommended to apply product over carpet, tile, or other types of floor adhesives.
- This product performs best when applied in very light coats. Do not puddle or apply in thick coats.
- Please be aware that this product when cured may be slippery when wet.
- This product is not resistant to brake fluid, gasoline, and many similar products.
- This product is not resistant to hot tire pick up.
- This product may darken the surface of many new and existing concrete slabs. Test prior to use.
- This product is harmful if swallowed. Abide by recommended safety guidelines.
- This product was designed for interior, foot traffic use only. It is not recommended for exterior use.
- This product should only be diluted for spray buffing only. Do not dilute for normal use.
- This product should only be used as a sacrificial coating and not used as a sealing compound.

## Special Notes

Please consult Safety Data Sheets (SDS) and read warranty information prior to use. This information can be requested by contacting customer service at 844-599-2319.

## Warranty

Super Z LLC dba Concrete Floor Supply warrants that our products and the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products and uses is not a representation or a warranty. It is supplied on the condition that you will make your own tests to determine the suitability of the product for your own particular purpose.

Any use or application is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications.

Concrete Floor Supply MAKES NO WARRANTY OR GUARANTEE, EXPRESSED OR IMPLIED, RELATING TO THE PRODUCTS AND THEIR APPLICATION. THIS INCLUDES WARRANTIES OF FITNESS, DESIGN COMPATIBILITY OR MERCHANTABILITY FOR ANY PARTICULAR USE AND SHALL HAVE NO RESPONSIBILITY OR LIABILITY, INCLUDING DIRECT, INDIRECT OR CONSEQUENTIAL DAMAGES, DUE TO INJURY, DELAY OR THIRD PARTY CLAIMS FOR INSTALLATION OR REPAIR.

Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. Upon receipt of merchandise, purchaser has 30 days to notify Concrete Floor Supply in writing that the materials are defective. Defective product means that it is not merchantable and has not been used. Claims after 30 days of purchase are void. Should any of Concrete Floor Supply products prove to be defective within the 30 days from the purchase date, Concrete Floor Supply, at its sole discretion will either replace the material, issue a credit, or provide a refund for the initial paid purchase price of the material.

Certain Products may contain chemicals which may cause serious physical injury. Before using, read the Materials Safety Data Sheet and follow all precautions to prevent harm.