

Concrete Renovator

Super Blue is a penetrating concentrated descaler and surface renovator that quickly penetrates and dissolves lime deposits, mortar, scale, rust algae, stains and mineral sediments.

Super Blue is the safe substitute for muriatic acid.

Type:	Penetrating acidic detergent renovator.
Toxicity:	Low, do not take internally.
VOC'S:	Low.
Flammability:	Non-Flammable.
Composition:	Biodegradable surfactants, inhibitors and acidic boosters.
Color:	Blue.
Odor:	Cherry.
Coverage:	Approximately 150 square feet per gallon without dilution. Approximately 450 square feet per gallon at a 1:3 ratio.



NOTE: COVERAGE RATES MAY VARY DEPENDING ON POROSITY, TEXTURE, APPLICATION METHOD AND PRIOR SEALER APPLICATION. EXCESS BUILDUP SHOULD BE AVOIDED.

Product Highlights

- Super Blue produces no harsh or irritating fumes even in interior areas where raw muriatic acid produces choking and corrosive fumes.
- Super Blue can be used at full strength on difficult stains. When used with staining we suggest 1:3 ratio (1-gallon super blue to 3-gallons of water) for optimum results.
- Super Blue works fast and efficiently with deep penetrating action that lifts off stains with a minimum of effort and no excess product wasted.
- Because it is a strong, surface-active penetrant rather than a harsh strong acid, Super Blue does the job faster, with less labor and less product.
- Most of the metal encountered on the job will be either steel or aluminum. Super Blue is highly inhibited against attack on these metals. It will brighten copper and brass but will not corrode them if washed off. It should not be used on magnesium, galvanized metal or stainless steel.

Product Uses

Super Blue is the safe replacement for muriatic acid to clean concrete, tile, brick and even glass and aluminum frames to remove lime, scale, excess mortar, algae and stains prior to sealing or staining concrete.

Instructions for Use

Super Blue may be applied by brush, dip or spray. (When spraying, use as coarse a pattern as possible to avoid inhalation of mist). Allow to soak for several minutes, agitate heavy soil or stains with stiff broom then rinse thoroughly with water. Repeat application may be necessary if heavy accumulation is present.

Note: Some types of stainless steel, chrome plating, porcelain on steel and polished decorative aluminum may be discolored. Test before using. Do not use magnesium or zinc (galvanized). Plastic or polyethylene sprayers and buckets are recommended for application. Depending on the type of stain or soil, Super Blue may be used full strength or diluted up to 1:4 with water. Allow to dry completely before staining or sealing

Storage and Disposal

Store at room temperature. Keep the container closed when not in use. Do not transfer contents to other containers for storage or disposal. Do not reuse empty container, wash with water and discard according to local, state and federal regulations.

Precautionary Statement

Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Store locked up. Dispose of contents/container according to local, state and federal regulations.

First Aid

IF INGESTED: Do not induce vomiting. Drink two glasses of water or milk. Get immediate Medical Help.

IF IN EYES: Flush thoroughly with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

IF ON SKIN: Rinse off thoroughly with water then soap and water. If irritation develops, Get Medical Help. Wash contaminated clothing before reuse.

IF INHALED: Remove to fresh air immediately. If breathing difficulty continues, Get Medical Help.

In Case of Fire

This Product is not flammable

Warranty

Super Z LLC dba Concrete Floor Supply warrants that our products and the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products and uses is not a representation or a warranty. It is supplied on the condition that you will make your own tests to determine the suitability of the product for your own particular purpose.

Any use or application is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications.

Concrete Floor Supply MAKES NO WARRANTY OR GUARANTEE, EXPRESSED OR IMPLIED, RELATING TO THE PRODUCTS AND THEIR APPLICATION. THIS INCLUDES WARRANTIES OF FITNESS, DESIGN COMPATIBILITY OR MERCHANTABILITY FOR ANY PARTICULAR USE AND SHALL HAVE NO RESPONSIBILITY OR LIABILITY, INCLUDING DIRECT, INDIRECT OR CONSEQUENTIAL DAMAGES, DUE TO INJURY, DELAY OR THIRD PARTY CLAIMS FOR INSTALLATION OR REPAIR.

Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. Upon receipt of merchandise, purchaser has 30 days to notify Concrete Floor Supply in writing that the materials are defective. Defective product means that it is not merchantable and has not been used. Claims after 30 days of purchase are void. Should any of Concrete Floor Supply products prove to be defective within the 30 days from the purchase date, Concrete Floor Supply, at its sole discretion will either replace the material, issue a credit, or provide a refund for the initial paid purchase price of the material.

Certain Products may contain chemicals which may cause serious physical injury. Before using, read the Materials Safety Data Sheet and follow all precautions to prevent harm.